



IBM

C2140-842

Rational Functional Tester for Java

QUESTION: 44

Which statement is true about the “Time Delayed” method when you are creating verification points in your scripts?

- A. It introduces a fixed delay after a previous action before the verification point is tested
- B. It allows a verification point to keep trying until the time specified has elapsed
- C. It gives the tester time to reveal pop-up objects (such as menus) during the creation of a verification point
- D. It gives the tester the opportunity to specify a delay after a verification point fails

Answer: C

QUESTION: 45

Given the following manual verification point `vpManual (“manual1”, “The rain in Spain”, “The Rain in Spain”).performTest();` What are the results?

- A. The two strings are the same, and a pass would be generated in the log
- B. The two strings are different, and a fail would be generated in the log
- C. The syntax is incorrect, so this would not compile
- D. This will compile but the parameters are mixed up, and a fail would be recorded in the log. The correct syntax is: `vpManual (“The rain in Spain”, “The Rain in Spain”, “manual1”).performTest();`

Answer: B

QUESTION: 46

Which branches under Preferences contain specific settings to enable the ClearCase integration?

- A. Workbench and Test
- B. Functional Test and Run/Debug
- C. Workbench and Team
- D. Plug-in Development and Functional Test

Answer: C

QUESTION: 47

When you set break points, why does the script not stop at the break points and switch over to the debug perspective?

- A. This is a known eclipse bug in version 6.1 and has been corrected in the latest release or last interim fix
- B. The break point has already been recognized by the JVM and the break point needs to be toggled
- C. Either the icon or debug functional tester script was not invoked or the shift + F11 menu option was not invoked
- D. The debug perspective is not listed as an available perspective when trying to debug a script

Answer: C

QUESTION: 48

When you enable web browsers, what is the best way to select the Linux or UNIX web browser?

- A. You use the Search button, choose Search All, select the executable, and provide all the needed parameters.
- B. Modify the registry to enable Linux or Unix web browser support
- C. Modify the Internet Explorer settings to refer to a Linux or Unix web browser
- D. You use the Search button, choose Search In, browse to the executable, and provide all the needed parameters

Answer: D

QUESTION: 49

In which situation is it best to use the Browser Enablement Diagnostic tool?

- A. when the web browser does not launch when invoked through Functional Tester

- B. when testers are trying to determine if their web browsers are compatible with Functional Tester
- C. when Functional Tester is in the recording process and no HTML objects are being recognized
- D. when Functional Tester is not able to launch the viewlet comparator on the HTML log

Answer: C

QUESTION: 50

You cannot access help file from Rational Functional Tester. You receive an error or the page loads slowly. How can this be fixed?

- A. talk to the LAN Administrator to see if there is a problem with the corporate network or if the ISP is having performance issues
- B. in Network properties, change the IP configuration to static IP and provide a valid IP address, which can be obtained from the LAN Administrator
- C. in the Network Advanced settings for proxies, remove “127.0.0.1; localhost” from the Exceptions if these addresses are listed
- D. if your host was configured to use DHCP for IP assignment, make sure that the “Automatically detect settings” checkbox is cleared

Answer: D

QUESTION: 51

Where do you set the option for switching to Test Debug perspective when debugging?

- A. Preferences > Functional Test > Workbench > Advanced
- B. Preferences > Java > Debug
- C. Preferences > Run/Debug > Console
- D. Preferences > Test

Answer: A

QUESTION: 52

How do you add line numbers within the script editors view?

- A. use a third party plug-in because this option is not available within the tools interface
- B. download the latest version of the plug-in
- C. select the option under the main menu > Window > Preferences > Debug
- D. select the option under the main menu > Window > Preferences > Editor

Answer: D

QUESTION: 53

How many default Java environments can you have within one configuration of Rational Functional Tester?

- A. one for each instance of the application under test
- B. as many default Java environments as are needed to do testing
- C. You can change the java environments dynamically when testing different applications.
- D. only one

Answer: D

QUESTION: 54

What is the best practice when changing object maps that are already assigned to Functional Test projects?

- A. highlight the project in the Functional Test projects, right-click, select Properties > Functional Test project and browse to the new object map
- B. record a new script, select the new Functional Test project, click next and browse to the new test object map
- C. modify the XML file, configurations.rftcfg, locate the object map section, enter the proper object and save the XML file
- D. right-click the test object map in the script explorer, choose the Open option and make necessary changes

Answer: A

Download Full Version From <https://www.certkillers.net>



Pass your exam at First Attempt....Guaranteed!